




## Edelstahl-Wellrohr

WS DN20 WW1010XX Material: 1.4404 / AISI 316L

spannungsfrei gegüht



	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13
mtr/ sec	0	0.493	0.618	0,741	0.819	0.936	1.035	1.126	1.239	1.316	1.383	1.428	1.513
lt/min	0	5.659	7.069	8.492	9.387	10.73	11.870	12.906	14.205	15.092	15.858	16.366	17.349
mbar/ mtr	0	1.298	2.132	3.105	4.264	5.562	7.138	8.899	10.753	12.792	15.017	17.381	19.884

Biegeradius min. statisch Bending radius min. static	mm	25	P1 / P2 Wellenbreite / Wavelength	mm	4.7
ØID Innendurchmesser / Inner Diameter	mm	20.1	Fläche / Surface Area	m <sup>2</sup> /mtr	0,139
ØOD Außendurchmesser / Outer Diameter	mm	25.5	Gewicht / Weight	kg/m	0,29
w Wandstärke / Wall thickness	mm	0,3	Volumen / Volume	l/mtr	0,44
max. Betriebsdruck max. operating pressure	bar	10	min. Querschnittsfläche Section Area	mm <sup>2</sup>	317.15
Wellen/mtr. / Corr./mtr.		213	Medium Wasser Medium Water 20°C	kg/m <sup>2</sup>	1000

