




## Edelstahl-Wellrohr

WR DN16 WW 2030XX Material: 1.4404 / AISI 316L

spannungsfrei gegläht



	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13
mtr/ sec	0	0.234	0.283	0.316	0.380	0.433	0.461	0.506	0.537	0.588	0.636	0.670	0.708
lt/min	0	2.680	3.246	3.623	4.355	4.973	5.286	5.799	6.161	6.748	7.289	7.689	8.122
mbar/ mtr	0	1.395	2.241	3.256	4.482	5.750	7.484	9.302	11.247	13.361	15.729	18.266	20.888

Biegeradius min. statisch Bending radius min. static	mm	20	P1 / P2 Wellenbreite / Wavelength	mm	5
Ø ID Innendurchmesser / Inner Diameter	mm	15.6	Fläche / Surface Area	m <sup>2</sup> /mtr	0,0712
Ø OD Außendurchmesser / Outer Diameter	mm	20.2	Gewicht / Weight	kg/m	0,190
w Wandstärke / Wall thickness	mm	0,3	Volumen / Volume	l/mtr	0,24
max. Betriebsdruck max. operating pressure	bar	10	min. Querschnittsfläche Section Area	mm <sup>2</sup>	191.04
Wellen/mtr. / Corr./mtr.		190	Medium Wasser Medium Water 20°C	kg/m <sup>2</sup>	1000

